

ES4 08 Series

Performance features at 50 Hz

PUMP MODEL	STAGES	P2		l/min m ³ /h	0	80	100	140	180	200
		kW	HP		0	4,8	6,0	8,4	10,8	12
ES4 08 04	4	0,75	1,0	mwc	26	24	22	19	15	12
ES4 08 06	6	1,1	1,5		39	36	34	29	22	17
ES4 08 08	8	1,5	2		52	48	46	39	29	24
ES4 08 13	13	2,2	3		82	75	71	59	40	30
ES4 08 17	17	3	4		108	98	94	79	58	46
ES4 08 21	21	3,7	5		132	117	111	93	68	52
ES4 08 23	23	4	5,5		148	134	127	108	79	60
ES4 08 32	32	5,5	7,5		202	182	172	143	105	80
ES4 08 43	43	7,5	10		272	244	230	193	141	107

ES4 08..04I Series

Dimensions and weights

ELECTROPUMP MODEL	STAGES	DNM	DIMENSIONS (mm)		PUMP WEIGHT	ELECTROPUMP WEIGHT
			L1	L	kg	kg
ES4 08 04 M 04I	4	RP/NPT 2"	294	674	2,8	11,8
ES4 08 06 M 04I	6	RP/NPT 2"	356	771	3,4	14,3
ES4 08 08 M 04I	8	RP/NPT 2"	418	868	4,0	16,5
ES4 08 13 M 04I	13	RP/NPT 2"	573	1073	5,5	20,3
ES4 08 04 T 04I	4	RP/NPT 2"	294	649	2,8	10,7
ES4 08 06 T 04I	6	RP/NPT 2"	356	736	3,4	12,4
ES4 08 08 T 04I	8	RP/NPT 2"	418	833	4,0	15,1
ES4 08 13 T 04I	13	RP/NPT 2"	573	1023	5,5	18,1
ES4 08 17 T 04I	17	RP/NPT 2"	697	1147	6,6	20,2
ES4 08 21 T 04I	21	RP/NPT 2"	859	1429	7,8	25,3
ES4 08 23 T 04I	23	RP/NPT 2"	921	1491	8,4	25,9
ES4 08 32 T 04I	32	RP/NPT 2"	1238	1868	11,0	32,0
ES4 08 43 T 04I	43	RP/NPT 2"	1603	2439	14,2	42,7

ES4 08..A4I Series

Dimensions and weights

ELECTROPUMP MODEL	STAGES	DNM	DIMENSIONS (mm)		PUMP WEIGHT	ELECTROPUMP WEIGHT
			L1	L	kg	kg
ES4 04 08 M A4I	4	RP/NPT 2"	294	580	2,8	11,0
ES4 08 06 M A4I	6	RP/NPT 2"	356	687	3,4	14,1
ES4 08 08 M A4I	8	RP/NPT 2"	418	811	4,0	16,5
ES4 08 13 M A4I	13	RP/NPT 2"	573	986	5,5	19,5
ES4 08 04 T A4I	4	RP/NPT 2"	294	560	2,8	10,4
ES4 08 06 T A4I	6	RP/NPT 2"	356	642	3,4	11,6
ES4 08 08 T A4I	8	RP/NPT 2"	418	766	4,0	15,8
ES4 08 13 T A4I	13	RP/NPT 2"	573	966	5,5	18,1
ES4 08 17 T A4I	17	RP/NPT 2"	697	1241	6,6	27,0
ES4 08 21 T A4I	21	RP/NPT 2"	859	1473	7,8	31,3
ES4 08 23 T A4I	23	RP/NPT 2"	921	1535	8,4	31,9
ES4 08 32 T A4I	32	RP/NPT 2"	1238	1922	11,0	37,8
ES4 08 43 T A4I	43	RP/NPT 2"	1603	2367	14,2	43,2

