

Lynx TE

LYNX-TE 32W/840 FSD

0027858



Product features

- Triple bend compact pin-base lamps, - Suitable for operation on electronic ballasts, - Excellent luminous flux, - Excellent colour rendering, - Dimmable with suitable dimmer



PRODUCT OVERVIEW

IPC Code	0027858
Product name	LYNX-TE 32W/840 FSD
Technology	Compact Fluorescent
Watt (Rated) (W)	32
Lamp shape	Other
Cap/Base	GX24q-3
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
Certifications	EUERL036
ETIM Class	EC000087
E-number FI	4944143
E-number SE	8357435
E-number Norway	3802808
Luminous flux (lm)	2400
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	82
Wattage (W)	32
Product Voltage (V)	220
Dimmable	No
Average life (Nominal) (h)	12000
Product EAN number	5410288278582

DATA TABLE

General data

IPC Code	0027858
Product name	LYNX-TE 32W/840 FSD
Technology	Compact Fluorescent
Watt (Rated) (W)	32
Lamp shape	Other
Cap/Base	GX24q-3
Lamp finish	Frosted/Coated

Lynx TE

LYNX-TE 32W/840 FSD

0027858

Fixture rating	Open
General application	Education,Hospitality,Logistics & Industry,Museums & Galleries,Office,Retail,Residential & Consumer
Certifications	EUERL036
ETIM Class	EC000087
E-number FI	4944143
E-number SE	8357435
E-number Norway	3802808

Optical data

Luminous flux (lm)	2400
Luminous flux (Rated) (lm)	2400
Rated lamp efficacy 100h 50Hz at 25°C (lm/W)	75
Rated lamp efficacy 100h 50Hz at optimum temp. (lm/W)	75
Rated lamp efficacy 100h HF at 25°C (lm/W)	75.00
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	82
Adjustable chromaticity	N
Rated lumen maint. factor (%) at 2000 h 50Hz	85
Rated lumen maint. factor (%) at 4000 h 50Hz	84
Rated lumen maint. factor (%) at 8000 h 50Hz	81

Electrical data

Wattage (W)	32
Starting time (max) (s)	0.1 Sec
Current (A)	0.32
Product Voltage (V)	220
Control gear required	Yes
Transformer required	No
Dimmable	No
Lamp Energy Label (class)	B
kWh per 1000 hours burning time	31

Lifetime data

Average life (Nominal) (h)	12000
Average life (Rated) (h)	12000
Rated survival factor (%) at 2000 h 50Hz	96
Rated survival factor (%) at 4000 h 50Hz	90
Rated survival factor (%) at 6000 h 50Hz	80
Rated survival factor (%) at 8000 h 50Hz	72

Lynx TE

LYNX-TE 32W/840 FSD
0027858

Rated survival factor (%) at 12000 h 50Hz	70
---	----

Physical data

Max. Length base to base (mm) - A	157
Max. Lamp Diameter (mm) - D	49
Weight (kg)	0.081


Packaging

Single packaging type	Carton
Product EAN number	5410288278582
Packaging single length / height (cm)	4.8
Packaging single width (cm)	4.5
Packaging single depth (cm)	15.6
DUN14 (outer)	15410288278589
Units per outer package	10
Packaging outer length / height (cm)	24.7
Packaging outer width (cm)	10.9
Packaging outer depth (cm)	17.5

Safety data

Lamp mercury content (mg)	3.5
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Intended purpose	General lighting
Dry applications use only	Yes
Suitable for household illumination	Yes

TECHNICAL DRAWINGS



Lynx TE
LYNX-TE 32W/840 FSD
0027858

