



Ref. Certif. No.

**ES1842-M2-AENOR**

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT  
(IECEE) CB SCHEME**

## CB TEST CERTIFICATE

Product

LED LUMINAIRES FOR EMERGENCY LIGHTING

Name and address of the applicant

LEGRAND GROUP ESPAÑA, S.L.  
CL HIERRO, 56  
28850 TORREJON DE ARDOZ (Madrid - Spain)

Name and address of the manufacturer

SAME AS ABOVE

Name and address of the factory

SAME AS ABOVE

Note: When more than one factory, please report on page 2

☐ Additional Information on page 2

Ratings and principal characteristics

SEE ANNEX

Trademark (if any)

LEGRAND

Customer's Testing Facility (CTF) Stage used

---

Model / Type Ref.

SEE ANNEX

Additional information (if necessary may also be reported on page 2)

☒ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60598-1:2020  
IEC 60598-2-22:2021  
IEC 62262:2002  
IEC 62262:2002/AMD1:2021

As shown in the Test Report Ref. No. which forms part of this Certificate

2025010002B1

This CB Test Certificate is issued by the National Certification Body

AENOR CONFÍA S.A.U.  
CI Génova, 6  
ES-28004 MADRID (SPAIN)

Date: 2025-05-26

Signature: Rafael GARCÍA MEIRO  
CEO

# ANNEX TO CB CERTIFICATE N° ES1842-M2-AENOR

## CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

### LED LUMINAIRES FOR EMERGENCY LIGHTING

| Type reference | Trade Mark | Rated voltage and frequency | N° lamps x rated power, type and lampholder | IP degree of protection | Power supply connection means | Classif. per holding surface material                                                    | Protection against electric shocks (class) | Rated lumen output and duration | Battery features                      | Additional information                                                | General data                                                     |
|----------------|------------|-----------------------------|---------------------------------------------|-------------------------|-------------------------------|------------------------------------------------------------------------------------------|--------------------------------------------|---------------------------------|---------------------------------------|-----------------------------------------------------------------------|------------------------------------------------------------------|
| 660620         | LEGRAND    | 230 V~; 50/60 Hz            | LED 2 x 0,25 W                              | IP 42; IK 07            | Bornes / terminals            | Apta para superficies normalmente inflamables / suitable for normally flammable surfaces | Clase / class II                           | 70 lm - 1 h                     | 2,4 V 0,8 Ah NiCd 2 elementos / cells | No permanente / non maintained; puesta en reposo remota / remote rest | Protección electrónica / electronic protection. URA-ONE Autotest |
| 660621         | LEGRAND    | 230 V~; 50/60 Hz            | LED 2 x 0,25 W                              | IP 42; IK 07            | Bornes / terminals            | Apta para superficies normalmente inflamables / suitable for normally flammable surfaces | Clase / class II                           | 100 lm - 1 h                    | 2,4 V 0,8 Ah NiCd 2 elementos / cells | No permanente / non maintained; puesta en reposo remota / remote rest | Protección electrónica / electronic protection. URA-ONE Autotest |
| 660623         | LEGRAND    | 230 V~; 50/60 Hz            | LED 4 x 0,25 W                              | IP 42; IK 07            | Bornes / terminals            | Apta para superficies normalmente inflamables / suitable for normally flammable surfaces | Clase / class II                           | 200 lm - 1 h                    | 2,4 V 1,5 Ah NiCd 2 elementos / cells | No permanente / non maintained; puesta en reposo remota / remote rest | Protección electrónica / electronic protection. URA-ONE Autotest |
| 660624         | LEGRAND    | 230 V~; 50/60 Hz            | LED 4 x 2 W                                 | IP 42; IK 07            | Bornes / terminals            | Apta para superficies normalmente inflamables / suitable for normally flammable surfaces | Clase / class II                           | 350 lm - 1 h                    | 3,6 V 1,5 Ah NiCd 3 elementos / cells | No permanente / non maintained; puesta en reposo remota / remote rest | Protección electrónica / electronic protection. URA-ONE Autotest |
| 660625         | LEGRAND    | 230 V~; 50/60 Hz            | LED 4 x 1 W                                 | IP 42; IK 07            | Bornes / terminals            | Apta para superficies normalmente inflamables / suitable for normally flammable surfaces | Clase / class II                           | 500 lm - 1 h                    | 4,8 V 2,0 Ah NiMH 4 elementos / cells | No permanente / non maintained; puesta en reposo remota / remote rest | Protección electrónica / electronic protection. URA-ONE Autotest |
| 661625         | LEGRAND    | 230 V~; 50/60 Hz            | LED 4 x 2 W                                 | IP 42; IK 07            | Bornes / terminals            | Apta para superficies normalmente inflamables / suitable for normally flammable surfaces | Clase / class II                           | 500 lm - 1 h                    | 4,8 V 2,0 Ah NiMH 4 elementos / cells | No permanente / non maintained; puesta en reposo remota / remote rest | Protección electrónica / electronic protection. URA-ONE          |
| 661637         | LEGRAND    | 120 V~; 50/60 Hz            | LED 4 x 0,25 W                              | IP 42; IK 07            | Bornes / terminals            | Apta para superficies normalmente inflamables / suitable for normally flammable surfaces | Clase / class II                           | 160 lm - 1 h                    | 3,6 V 1,5 Ah NiCd 3 elementos / cells | No permanente / non maintained; puesta en reposo remota / remote rest | Protección electrónica / electronic protection. URA-ONE 120VAC   |
| 661638         | LEGRAND    | 120 V~; 50/60 Hz            | LED 4 x 1 W                                 | IP 42; IK 07            | Bornes / terminals            | Apta para superficies normalmente inflamables / suitable for normally flammable surfaces | Clase / class II                           | 350 lm - 1 h                    | 4,8 V 1,5 Ah NiCd 4 elementos / cells | No permanente / non maintained; puesta en reposo remota / remote rest | Protección electrónica / electronic protection. URA-ONE 120VAC   |

# ANNEX TO CB CERTIFICATE N° ES1842-M2-AENOR

## CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

| Type reference | Trade Mark | Rated voltage and frequency | N° lamps x rated power, type and lampholder | IP degree of protection | Power supply connection means | Classif. per holding surface material                                                    | Protection against electric shocks (class) | Rated lumen output and duration | Battery features                      | Additional information                                                                                          | General data                                                |
|----------------|------------|-----------------------------|---------------------------------------------|-------------------------|-------------------------------|------------------------------------------------------------------------------------------|--------------------------------------------|---------------------------------|---------------------------------------|-----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|
| 661640         | LEGRAND    | 230 V~; 50/60 Hz            | LED 4 x 0,5 W                               | IP 42; IK 07            | Bornes / terminals            | Apta para superficies normalmente inflamables / suitable for normally flammable surfaces | Clase / class II                           | 100 lm - 3 h                    | 4,8 V 2,0 Ah NiMH 4 elementos / cells | Permanente , posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest | Protección electrónica / electronic protection. URA-ONE     |
| 662640         | LEGRAND    | 230 V~; 50/60 Hz            | LED 4 x 0,5 W                               | IP 42; IK 07            | Bornes / terminals            | Apta para superficies normalmente inflamables / suitable for normally flammable surfaces | Clase / class II                           | 100 lm - 3 h                    | 4,8 V 2,0 Ah NiMH 4 elementos / cells | Permanente , posible no permanente / maintained, possible non maintained; puesta en reposo remota / remote rest | Protección electrónica / electronic protection. URA-ONE LVS |